



Steel enclosures made from a continuous length of sheet steel double folded at the front, with back welded to the frame. Both externally and internally protected with polyester epoxy resin grey paint to RAL-7032 texturised.

- **CRN...KT** series includes a transparent tempered glass door.
- mounting plate supports are depth adjustable.
- reinforced sections in solid doors with drill holes for wiring, from model **CRN-54/200** upwards.
- reversible door, opening 120° in either direction.
- possibility of mounting the enclosure on a **ZUN** plinth (100 and 200 mm. high) in the case of 600, 800 and 1000mm. wide by 300 mm. deep models.

external dimensions (mm)			enclosures					mounting plates				DINIMEL frame	19" fixed and swing frames	Internal door	
Height (A)	Width (B)	Depth (C)	product reference	product reference with transparent door	fig.	cable entry	weight * (Kg)	metal	insulating	perforated	universal	movable plate support			
250	200	150	CRN-2520/150	-	1	0	3,2	●	●	●					
300	250	150	CRN-3025/150	CRN-3025/150 KT	1	A	4,2	●	●	●	●		●		
300	250	200	CRN-3025/200	CRN-3025/200 KT	1	A	4,9	●	●	●	●	●	●		
300	300	150	CRN-33/150	CRN-33/150 KT	1	B	5	●	●	●	●				
300	300	200	CRN-33/200	CRN-33/200 KT	1	B	6	●	●	●	●	●			
300	400	200	CRN-34/200	CRN-34/200 KT	1	C	6,4	●	●	●	●	●			
400	300	150	CRN-43/150	CRN-43/150 KT	1	B	6	●	●	●	●		●	○	
400	300	200	CRN-43/200	CRN-43/200 KT	1	B	6,8	●	●	●	●	●	●	○	
400	400	200	CRN-44/200	CRN-44/200 KT	1	C	8	●	●	●	●	●			●
400	600	250	CRN-46/250	CRN-46/250 KT	1	D	10	●	●	●	●	●			●
400	600	300	CRN-46/300	CRN-46/300 KT	1	D	11,2	●	●	●	●	●			●
500	400	150	CRN-54/150	CRN-54/150 KT	2	B	8,7	●	●	●	●	●	●	○	
500	400	200	CRN-54/200	CRN-54/200 KT	2	C	9,8	●	●	●	●	●	●	○	●
500	400	250	CRN-54/250	CRN-54/250 KT	2	C	11	●	●	●	●	●	○		●
500	500	250	CRN-55/250	CRN-55/250 KT	2	D	12,8	●	●	●	●	●			●
600	400	150	CRN-64/150	CRN-64/150 KT	2	B	9,3	●	●	●	●	●	●	○	
600	400	200	CRN-64/200	CRN-64/200 KT	2	C	10,8	●	●	●	●	●	●	○	●
600	400	250	CRN-64/250	CRN-64/250 KT	2	C	12,3	●	●	●	●	●	○		●
600	500	150	CRN-65/150	CRN-65/150 KT	2	B	11,3	●	●	●	●	●	●		●
600	500	200	CRN-65/200	CRN-65/200 KT	2	D	14,3	●	●	●	●	●	●		●
600	500	250	CRN-65/250	CRN-65/250 KT	2	D	16,3	●	●	●	●	●			●
600	600	200	CRN-66/200	CRN-66/200 KT	2	D	-	●	●	●	●	●	●		●
600	600	250	CRN-66/250	CRN-66/250 KT	2	D	18,2	●	●	●	●	●	●	○	●
600	600	300	CRN-66/300	CRN-66/300 KT	2	D	19,8	●	●	●	●	●	●	○	●
600	800	300	CRN-68/300	CRN-68/300 KT	2	E	26	●	●	●	●	●	●		●
700	500	200	CRN-75/200	CRN-75/200 KT	2	D	17,3	●	●	●	●	●	●	○	●
700	500	250	CRN-75/250	CRN-75/250 KT	2	D	19,3	●	●	●	●	●	●	○	●
800	600	200	CRN-86/200	CRN-86/200 KT	2	D	21,8	●	●	●	●	●	●	○	●
800	600	250	CRN-86/250	CRN-86/250 KT	2	D	24,8	●	●	●	●	●	●	○	●
800	600	300	CRN-86/300	CRN-86/300 KT	2	D	26,3	●	●	●	●	●	●	○	●
800	600	400	CRN-86/400	CRN-86/400 KT	2	D	-	●	●	●	●	●	●	○	●
800	800	200	CRN-88/200	CRN-88/200 KT	2	E	29,5	●	●	●	●	●	●		●
800	800	300	CRN-88/300	CRN-88/300 KT	2	E	32,5	●	●	●	●	●	●		●
800	1000	300	CRN-810/300**	-	4	E	37	●	●	●	●	●	●		●
1000	600	250	CRN-106/250	CRN-106/250 KT	2	D	28,4	●	●	●	●	●	●	○	●
1000	600	300	CRN-106/300	CRN-106/300 KT	2	D	30,6	●	●	●	●	●	●	○	●
1000	800	250	CRN-108/250	CRN-108/250 KT	2	E	34,5	●	●	●	●	●	●	○	●
1000	800	300	CRN-108/300	CRN-108/300 KT	2	E	37,4	●	●	●	●	●	●	○	●
1000	800	400	CRN-108/400	CRN-108/400 KT	2	E	-	●	●	●	●	●	●	○	●
1000	1000	300	CRN-1010/300**	CRN-1010/300 KT	4 (KT:3)	F	46,7	●	●	●	●	●	●		●
1000	1200	300	CRN-1012/300**	-	4	F	41	●	●	●	●	●	●		●
1200	800	300	CRN-128/300**	CRN-128/300 KT	3	F	-	●	●	●	●	●	●		●
1200	800	400	CRN-128/400	CRN-128/400 KT	3	F	-	●	●	●	●	●	●		●
1200	1000	300	CRN-1210/300**	-	4	F	53,4	●	●	●	●	●	●		●
1200	1000	400	CRN-1210/400**	CRN-1210/400 KT	4	F	-	●	●	●	●	●	●		●

* Weight of enclosures with normal door. ** Enclosures with triple action lock

● Dinimel DL
○ Dinimel DLM



Enclosures with transparent tempered glass door, maintaining IP-55 protection.



Movable plate support with positions every 12.5 mm. Front part has M6 ø drill holes to enable various items to be fitted.



Close up of back of enclosure with 4 M8 x15 welded studs for fixing the mounting plate, and wall fixing holes closed with plastic plugs.



Two M6 x 15 welded earth pins on the base and a M6 x 15 pin in the door.

Dimensions (mm.)

